



**Industrial Equipment**  
Electron Beam Metal AM Machine

Solutions for Innovation

# JAM-5200EBM

Electron Beam Metal 3D Printer  
JEOL Additive Manufacturing Technology



JEOL Ltd.

We are  
changing the world  
with Electron Beam



## A little trip into space

Space travel, which was only a story in science fiction movies, is about to become a reality. Yet, it is still not something that anyone can easily afford. One of the reasons space travel is so expensive is because of the cost of traveling by rocket.

JEOL's electron beam additive manufacturing technology has the potential to drastically reduce the cost of rocket development, manufacturing, and even fuel.

The electron beam metal AM machine "JAM-5200EBM" makes it possible to reduce fuel consumption and increase output, reduce the cost, and shorten development time by high quality and high repeatability modeling, integration of multiple parts, and weight reduction. Together with JEOL's additive manufacturing technology, innovation is advancing at an unprecedented speed.

Making "a little trip into space" a reality. We are changing the world with Electron Beam.





\* Specifications and appearance are subject to change without notice.

Certain products in this brochure are controlled under the "Foreign Exchange and Foreign Trade Law" of Japan in compliance with international security export control. JEOL Ltd. must provide the Japanese Government with "End-user's Statement of Assurance" and "End-use Certificate" in order to obtain the export license needed for export from Japan. If the product to be exported is in this category, the end user will be asked to fill in these certificate forms.



3-1-2 Musashino Akishima Tokyo 196-8558 Japan Sales Division Tel. 81-3-6262-3561 Fax. 81-3-6262-3577  
www.jeol.com ISO 9001 • ISO 14001 Certified

• AUSTRALIA & NEW ZEALAND • BELGIUM • BRAZIL • CANADA • CHINA • EGYPT • FRANCE • GERMANY • UNITED KINGDOM (UK) • INDIA • ITALY • KOREA • MALAYSIA • MEXICO • RUSSIA  
• SWEDEN • SINGAPORE • TAIWAN • THAILAND • THE NETHERLANDS • UNITED ARAB EMIRATES (UAE) • UNITED STATES OF AMERICA (USA)


▼ Local office



No.5003L537X(Bn)

# JAM-5200EBM

## Electron Beam Metal 3D Printer



### ■ Long-life Cathode


The Long-life Cathode which lasts over 1,500 hours\*, can greatly reduce downtime for cathode replacement.

\* Ti-6Al-4V material



### ■ Powder dispersal prevention system "e-Shield"

No inert gas such as helium is required to prevent scattering of powder (smoke).



### ■ Automatic Electron Beam Correction

The spot shape and focus of the electron beam are automatically corrected over the entire build area.



### ■ Remote Monitoring System

The manufacturing status and the machine conditions can be checked from a remote location at any time.

## Electron Beam Powder Bed Fusion Printer (EB-PBF)

### High power 6 kW electron beam source

The printer has a more powerful electron beam source compared to laser sources. In addition to its high power, the electron beam features a fast scanning speed enabled by electromagnetic deflection and its thermal energy conversion efficiency is 80% or more for most metal materials, resulting in a high build speed. It is suitable for producing larger parts or a large number of smaller parts at once.

### Reduction of residual stress by hot process

High-temperature preheating with high-speed electron beam scanning reduces residual stress, which prevents cracking and deformation of parts. No heat treatment is required to reduce internal stress after the build.

### Reduction of oxygen, inert gas, and moisture effects by vacuum process

Since parts are built in a vacuum, the effects of residual oxygen and moisture are prevented. This makes it possible to build with even active metals such as titanium alloys. Additionally, because there is no need to introduce inert gas during the build, a clean high vacuum can be maintained.

### High quality production


The Long-life Cathode of 1,500 hours or more and the high-precision automatic beam correction function ensure highly reproducible build quality over the entire build area. In addition the printer met AMS7032 qualification requirements, an industrial standard for qualifying AM machines for the production of aerospace parts using Ti-6Al-4V material.

## Main Specifications


Manufacturing method	Powder bed fusion
Manufacturing dimensions	Maximum 250 mm (Dia.) × 400 mm (H)*
Electron beam output	Maximum 6 kW
Process	Hot process
Powder bed surface heating	Maximum 900 °C (standard specification) Maximum 1,200 °C (high-temperature specification)
Lifetime of cathode	1,500 h or longer (Ti-6Al-4V material)
Powder particle diameter (standard)	Approximately 45 to 105 μm
Layer thickness	50 μm / 75 μm
Powder dispersal prevention system	e-Shield
Beam correction	Automatic (Focus, Astigmatism, Distortion)
Chamber pressure (during melting)	0.01 Pa or lower
Data format	STL
Power supply	3-phase, 200 V (±10%), 35 kVA

\* The maximum manufacturing dimensions differ depending on the build material.

## Dimensions



## Powder Recovery System



## Build processes



After the build chamber is evacuated, the base plate is preheated and a layer of metal powder is spread.



The powder bed surface is preheated with an electron beam, and then focused to melt the part.



The base plate is lowered by one layer, and the process of spreading, preheating, and melting and solidifying the powder is repeated.



After the completed build is cooled, the part is depowdered by blasting in a Powder Recovery System. The recovered powder can be sieved and reused in future builds.

## Build material examples



### Titanium alloy (Ti-6Al-4V)

Distortion is suppressed and supportless parts possible.



### Nickel alloy 718

High creep strength is achieved by controlling the microstructure.



### Pure copper

101% IACS conductivity is achieved by high-density builds.



### Pure tungsten

High-density parts with minimal/no crack formation

\* Specifications and appearance are subject to change without notice.

Certain products in this brochure are controlled under the "Foreign Exchange and Foreign Trade Law" of Japan in compliance with international security export control. JEOL Ltd. must provide the Japanese Government with "End-user's Statement of Assurance" and "End-use Certificate" in order to obtain the export license needed for export from Japan. If the product to be exported is in this category, the end user will be asked to fill in these certificate forms.

