

VB-GX SERIES VIDEOSCOPE

- Exceptional image clarity, with low maintenance costs
- 720P or 1080P Image with 120° Field of View
- New Touch Screen Display Photo and Video Image Capture
- Image Enhancement feature
- Interchangeable Probe Modules with tungsten braiding
- Servo-assisted Articulation with push-button damping
- Side View 90° DOV and Dual View options
- Magnification 5 X Zoom
- 5" LCD Monitor with 5-step Adjustable Illumination
- Upgraded 9000 mah Lithium Ion Battery with Inductive Charging Cradle
- Insertion Tube temperature resistance (air) to 100° for 5 minutes (70° thereafter) for Ø4.0mm and Ø6.0mm models
- IP67 Rated available



Probe Module Part References (use with VB-GX-H Handset) :-

- **UF-6260X-DV** : Ø6.2mm x 6000mm System (Dual View, 4-Way Articulation) ~ Mechanical Articulation
- **UF-6235X-DV** : Ø6.2mm x 3500mm System (Dual View, 4-Way Articulation)
- **UF-3920X-DV** : Ø3.9mm x 2000mm System (Dual View, 4-Way Articulation)
- **UF-3920X** : Ø3.9mm x 2000mm System (0° DOV, 4-Way Articulation)
- **UF-3920X-90** : Ø3.9mm x 2000mm System (90°, 4-Way Articulation)
- **UF-2815X** : Ø2.8mm x 1500mm System (0° DOV, 4-Way Articulation)*
- **UF-2815X-90** : Ø2.8mm x 1500mm System (90° DOV, 4-Way Articulation)*
- **UF-2415X** : Ø2.4mm x 1500mm System (0° DOV, 4-Way Articulation)*
- **UF-2015X** : Ø2.0mm x 1500mm System (0° DOV, 2-Way Articulation)*
- **UF-2015X-90** : Ø2.0mm x 1500mm System (90° DOV, 2-Way Articulation)*
- **UF-1010X** : Ø1.0mm x 1000mm System (0° DOV, Non-Articulation)*
- **UF-0810X** : Ø0.85mm x 1000mm System (0° DOV, Non-Articulation)**

*stainless steel braiding, IP64 rated

**plastic probe cable